

4K H.265 Pro NVR 5000 Series


[DATASHEET](#)

KEY FEATURES

- ▶ **Powerful Decoding Capacity** (Maximum supporting 8*1080P or 16*720P for Milesight Pro NVR 5000 Series.)
- ▶ **HDMI & VGA** (Providing both HDMI and VGA ports for users to choose according to their monitor types.)
- ▶ **2*3.5"HDD** (2 SATA of 3.5"HDD, providing 10TB capacity for each HDD, up to 20TB total hard disk storage.)
- ▶ **Video Content Analysis** (With 10 detection modes, VCA greatly enhances the performance bringing comprehensive surveillance functions.)

H.265+H.264

Smartly figure out and switch between H.264 and H.265 automatically. It will extend the days to save recording file with H.265 than with other compressions.



4K Video Viewing Experience

Milesight 4K H.265 Pro NVR 5000 Series supports up to 4K definition (3840*2160, effectively four times that of Full HD) live viewing, playback and recording, providing users with ultra-high-definition video viewing experience.



Powerful Decoding Capacity

Maximum supporting 8*1080P or 8*720P for MS-N5008-UT, 8*1080P or 16*720P for MS-N5016-UT.



Remote Access

Milesight 4K H.265 Pro NVR 5000 Series can be easily accessed and managed remotely via Milesight CMS and mobile APP.






Model			MS-N5008-UT	MS-N5016-UT
Video/Audio Input	Network Video Input		8-CH	16-CH
	Bandwidth	Incoming	80Mbps	160Mbps
		Outgoing	80Mbps	160Mbps
Video/Audio Output	HDMI Output		1-CH, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI Supports Audio Output	
	VGA Output		1-CH, Resolution: 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
	Dual Stream		Support	
	Recording Resolution		8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF	
	Synchronous Playback		2*(30fps @8MP), 2*(30fps @6MP), 3*(30fps @5MP), 4*(30fps @4MP), 5*(30fps @3MP), 8*(30fps @1080P), 8*(30fps @720P)	2*(30fps @8MP), 2*(30fps @6MP), 3*(30fps @5MP), 4*(30fps @4MP), 5*(30fps @3MP), 8*(30fps @1080P), 16*(30fps @720P)
Video/Audio Compression	Video Compression		H.265 ⁺ /H.265(HEVC)/H.264 ⁺ /H.264	
	Audio Compression		G.711/AAC	
	Sample Rate		8KHz/16KHz	
	Synchronous Recording		8*5MP	16*5MP
Storage	SATA		2*SATA HDD(3.5")	
	Capacity		Up to 10TB capacity for each HDD	
Recording Management	Recording Type		Continuous, Motion Detection, Alarm, Smart Event, Event (Motion Detection, Alarm, Smart Event)	
	Snapshot		Manual Snapshot	
	Playback		Video Playback, Image Playback	
Backup	Backup		Video Backup, Image Backup	
Network	Protocol		IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS	
External Interface	Network Interface		1*RJ45 100M/1000M	
	USB Interface		1*USB 3.0; 2*USB 2.0	
	Audio Input/Output		— /1*RCA	
	Alarm Input/Output		4-CH/1-CH	
General	Compatibility		ONVIF	
	Video Analysis		Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting	
	Keyboard Control		Milesight Keyboard (MS-K02)	
	Power Supply		DC 12V 50Hz~60Hz	
	Consumption		≤10W(Without HDD)	
	Working Conditions		Temperature: -10℃~+55℃ Humidity: 10%~90%	
	Dimensions		Rack Mountable Chassis (1.0U Standard) 440mm(W)X251mm(D)X44.4mm(H)	
	Weight		2.6Kg	
	Warranty		3/5 Years	

4K H.265 Pro NVR 5000 Series




Interfaces



- | | | | | | | | |
|------------------|------------------|--------------------|---------|------------------|--------|---------|--------|
| 1. Run Indicator | 2. HDD Indicator | 3. Power Indicator | 4. USB | 5. Audio Out | 6. VGA | 7. HDMI | 8. USB |
| 9. Ethernet Port | 10. Alarm In/Out | 11. Power | 12. GND | 13. Power Button | | | |

Structure Diagrams



Units: mm

Naming Convention



Mlesight Technology Co.,Ltd. | www.mlesight.com

Contact Us: sales@mlesight.com support@mlesight.com

Add: 220 NE 51st Street, Oakland
Park, Florida 33334, USA
Tel: +1-800-561-0485

Add: 925, Anyang SK V1 Center, LS-ro
116beon-gil, Dongan-gu, Anyang-si, Korea
Tel: +82-31-990-7772

Add: No.23 Wanghai Road,
2nd Software Park, Xiamen, China
Tel: +86-592-5922772

